



# MANTA 16 / 20

FLUSH MOUNT CEILING

location:  
**DAMP**

## SPECIFICATIONS:

### DESCRIPTION

Ultra low profile ceiling luminaire, featuring handcrafted glass.

### LAMPING

**Halogen:** 40W low-pressure G9 Halogen 120V lamps, included.

**LED:** 16W Integrated source, 120V, dimmable, 85+ CRI, 3000°K CCT, 1500 lumens, 30,000 hours, included. (For Manta 16 only)

**LED:** 24W Integrated source, 120V, dimmable, 85+ CRI, 3000°K CCT, 2500 lumens, 30,000 hours, included. (For Manta 20 only)

### DIFFUSER

A multi-layered glass, with a Glossy White diffuser applied to a Clear glass ring.

**Manta 13 #9129XX:** 13.5" Dia. x 3" H

**Manta 18 #9130XX:** 17.75" Dia. x 3" H

### MOUNTING

Installs directly to a 4" octagonal outlet box, centered on fixture.

90°C supply wire required for incandescent lamping.


### LABELS

UL or ETL Listed. Suitable for Damp Locations (interior use only).




MANTA CEILING SHOWN IN OPAL GLOSSY

Manta 13: #9129



Manta 18: #9130



FIXTURE/DECOR	LAMP OPTIONS
912939C 13.5" Dia. Opal Glossy	<b>HAL</b> 2x 40W G9 Hal <b>LED</b> 16W LED 120V, 1500 lumens

FIXTURE/DECOR	LAMP OPTIONS
913039C 17.75" Dia. Opal Glossy	<b>HAL</b> 3x 40W G9 Hal <b>LED</b> 24W LED 120V, 2500 lumens

**Ex. 912939C-HAL**  
Manta 13 Ceiling w/ Opal Glossy Glass

Project Information:

All dimensions provided are nominal. Allowance must be made for dimensional tolerance in handcrafted glasses.